

# Machine Series: KPM-Premium

Case Sealer & Case Erector (automatic)



Fig. KAR-20TX

Production Speed:  
Up to 25 pcs / min

Fig. KPM-105SDR



Fig. KPM-30T



## Machine Information:

- Easy to maintain, low spare parts costs
- Adjustable tape tension
- 2 adhesive tape dispensers (top / bottom)
- Fast format change by hand wheel or light barrier technology
- Including product infeed and outfeed roller conveyor
- Self-adhesive tapes with 50mm width (optional 75mm)
- Conveyor belt running direction (right / left)
- Height adjustable feet on castors
- Case erector (KPM-116) available on request



Model	KPM-103SD	KAR-30T	KAR-20TX	KAR-20TK
	Case Sealer	Case Erector (horizontal)	Case Erector (vertical)	Case Erector (vertical)
Applicable tape:	PP, PVC, Hotmelt	PP, PVC, Hotmelt	PP, PVC, Hotmelt	PP, PVC, Hotmelt
Max. tape diameter:	410 mm	-	-	-
Tape width:	50 - 72 mm	48 - 72 mm	48 - 72 mm	48 - 72 mm
Min. case dimensions (L x W x H):	110 x 120 mm*	280 x 180 x 100 mm*	280 x 160 x 285 mm*	280 x 160 x 285 mm*
Max. case dimensions (W x H) <sup>2</sup> :	600 x 600 mm*	420 x 280 x 370 mm*	600 x 400 x 620 mm*	600 x 400 x 620 mm*
Max. case weight (approx.):	40 kg	-	-	-
Arrangement of the drive belts:	lateral	-	-	-
Case format adaption:	automatic	-	-	-
Transport speed:	23 m / min	5 - 10 m / min	20 - 25 m / min	-
Maximum reel height:	880 mm	-	-	-
Supply voltage:	230V	230V	230V	230V
Air pressure (dry air):	6.0 bar	6.0 bar	6.0 bar	6.0 bar
Max. connected load:	0,40 kW	0,40 kW	0,40 KW	0,40 KW
Machine weight (approx.):	195 kg	1000 kg	500 kg	550 kg
Production speed:	Up to 20 pcs / min	Up to 25 pcs/min	Up to 10 pcs/min	Up to 15 pcs/min