

# Machine Series: URM

Strapping Machine (automatic)



Customized frame sizes  
are possible on request



## Machine information:

- integrated strap storage, automatic strap transport
- user-friendly workflow
- high throughput due to microprocessor control
- adjustable strap tension (manual / electronic)
- fast strap change system ( manual / electronic )
- height adjustable feet on castors
- low-noise locking unit

## Further information:

### Properties (depending on model)

- Electrical voltage regulation
- No cardboard - no tension
- Automatic threading of the strap
- Loop ejection
- 2. strap return
- Free access to the strap guide
- Sensor controlled heating plate
- Adjustable table height

### Options

- Photosensor
- Foot Switch
- Frame Sensor



PP strapping band directly available,  
also printed with company logo

Model	URM-135	URM-137	URM-138	URM-158
Max. strap width:	5 mm*	9 – 12 mm*	9 – 15 mm*	9 – 15 mm*
Strap tension:	1 – 35 kg	1 – 58 kg	5 – 65 kg	5 – 65 kg
Max. connected load:	100/110/220/230/ 240 V, 50Hz, 1 phase	100/110/220/230/ 240 V, 50Hz, 1 phase	100/110/220/230/ 240 V, 50Hz, 1 phase	100/110/220/230/ 240 V, 50Hz, 1 phase
Power consumption:	0,70 kW	0,70 kW	0,60 kW	0,60 kW
Packing capacity:	Up to 60 straps / min**	Up to 55 straps / min**	Up to 36 straps / min**	Up to 36 straps / min**